

"Plymouth-La Rochelle Revival 2012" - Inspection Card

Name of the boat :	Sail No :	Nationality:
Number of crew :	Liferaft total capacity:	Call sign :
Name of the skipper :		MMSI :
Date:	Signature:	

Types of items :

R : Required

RE : Required, possible exception

HR : Highly Recommended regarding to the race conditions

Item	OSR	Type	Comments	Accordance
CREW SAFETY AND ALERT				
Liferaft with a valid certificate	4.20	R	Capacity to accommodate the number of persons on board, end of liferaft painter permanently fastened to the boat	
Lifejackets	5.01	R	Level 150N, one for each person on board, marked with the name of the vessel and with retro-reflective material	
Safety Harness and Safety Lines	5.02	R	One for each person on board, lines length 2m max, including 2 with mid-point snaphook	
Personal location lights (flashing)		R	Min: 1 for each person on deck (night)	
Safety lines clipping points	4.04	R	Min: 2 in the cockpit + 1 for the helmsman	
Jackstays	4.04	R	Permanently installed. According to chapter 4.04 (OSR ISAF)	
Lifebuoy with a self-igniting light	4.22	R	On deck, ready for instant use, marked with the name of the vessel	
Man overboard recovery device (ex: Lifesling)	4.22	HR	On deck, ready for instant use	
First Aid manual	4.08	HR	Or crew member familiar with First Aid procedures	
First Aid kit	4.08	R	Suited to the number of persons, at least according to French regulations	
Red parachute flares	4.23	R	Min 4, valid in date	
Red hand flares	4.23	R	Min 4, valid in date	
Orange smoke	4.23	R	Min 2 , valid in date	
Radio beacon EPIRB or GPIRB	4.19	HR	GPIRB model recommended	
Pulpits, Stanchions, Lifelines	3.14	RE	Required, according to chapter 3.14 (OSR ISAF). Possible exceptions, case by case basis, with a commitment from the skipper	
Toe Rail or Foot-Stop	3.17	R	H min: 20 mm	
High-powered flashlight/spotlight	4.07	R	Watertight, spare batteries and bulbs	
Flashlight	4.07	R	Watertight, spare batteries and bulbs	
Cockpit knife	4.25	R	Accessible from the deck or cockpit	
Ladder or device for reboarding		R	Permanently installed or removable	
ON BOARD SAFETY				
Fire extinguishers	4.05	R	Dry powder model, at least two, 2 Kgs each	
Foghorn	4.09	R		
Anchors with chain and rope	4.06	R	1 main anchor with min 40 m of chain or a suitable combination of chain and rope, 1 secondary anchor with chain and rope. Anchors must be securely fastened	
Emergency tiller	4.15	RE	Not required in case of metal tiller	
Storm jib	4.26	R		
Storm main sail	4.26	HR		

Standing rigging cutter	4.16	R	Size suitable for the diameter of standing rigging
Hatches watertightness	3.08	R	Outward opening hatches must be capable of being firmly shut
Other openings watertightness	3.02	R	Non-watertight openings should be blocked if necessary (ex: Grey-Tape use)
Companionway hatch	3.08	R	Drip-proof, locking operable from the exterior and from the interior.
Self-draining cockpit	3.09	R	All openings to the hull must be watertight when closed
Sea Cocks or valves	3.10	R	In good condition. Suitable soft wood plugs available near each opening (tied on if possible)
Soft wood plugs	4.03	R	
Bilge pumps	3.23	R	One permanently installed manual bilge pump operable from on deck and a second manual or electric one recommended. Must discharge overboard and not into the cockpit
Buckets	3.23	R	2 buckets >= 9 litres capacity each, with a lanyard
Floorboard/soleboard fixing	2.03	R	Floorboards/Soleboards to be secured in place
Gas bottle stowage	2.03	R	Gas bottles to be secured in place
Cooking stove	3.20	R	Permanently installed or securely fastened
Drinking water tank	3.21	R	Permanently installed water tank with delivery pump. Water in sufficient quantity for the crew (min 3 litres per day/person)
Emergency drinking water	3.21	R	>= 9 litres in a dedicated container
Propulsion engine and fuel	3.28	R	The main engine and the fuel on board the boat must allow the boat to reach on its own the nearest port, at any point in this race
Batteries	3.28	R	Sealed batteries if installed later than 1/1/2012. Separate battery to start the engine
Warps		R	Warps as needed, one suitable for trailing
Toilet	3.18	R	Permanently installed or fitted bucket
Tools	4.16	R	Hammer, screw driver, pliers...
NAVIGATION SAFETY			
Compass	3.24	R	Permanently installed
Second compass	3.24	R	hand-held steering and bearing compass
GPS	3.29	R	Powered by ship's supply
VHF	3.29	R	25 Watt power
MMSI number		HR	Required if EPIRB
Charts (paper)	4.11	R	For the race area
Broadcast radio receiver		R	for receiving weather forecasts
Navigation lights	3.27	R	See ISAF OSR 3.27
Reserve navigation lights	3.27	R	Independent power source accepted
Navigation lights spare bulbs	3.27	R	As appropriate
Spare VHF antenna	3.29	R	
Hand-held VHF transceiver	3.29	R	Watertight or with a waterproof cover
Radar reflector	4.10	R	Effective height above water > 4 m
Sail letters and numbers	4.01	R	Displayed on mainsail
List of Lights document (south UK and France)	4.11	R	Official document or a 2012 marine almanac including this list
Navigation documents		R	According to regulations and the race area
Depth sounder	4.13	R	Echo sounder or lead line
Speed and Distance Log	4.14	R	
AIS receiver or transponder (Tx/Rx) or radar alert system	3.29	HR	Highly recommended in view of the navigation area (channel traffic separation zones)
Safety equipment location chart	4.12	R	Waterproof material, displayed where it can best be seen